



TURNING BLAND TO GRAND

Technical Data Sheet

NoLite 165

Material Details		
Base Fabric	Polyester composite foil	
Thickness	165 µm	6.5 mil
Weight	225 g/m ²	6.64 oz/yd ²
Finish	Matte coating	
Storage conditions	Store boxed at 10 –35°C (50 –95°F)	
Processing Conditions	18° - 25°C (64° - 77°F)	
Shelf Life	12 months	

Special Features / Characteristics

- High opacity film with silver light blocking backer
- Matte finish to eliminate glare under fluorescent/interior lighting
- Scratch resistant inkjet coating
- Excellent print quality
- Fast drying
- Part of SEAL's INDISPLAY Solutions

Areas of Application

- Roll Up and 4 Screen display systems
- Trade show and exhibit graphics
- Suitable for indoor and for short term outdoor application use

Process & Handling

- To avoid fingerprints, usage of cotton gloves is recommended
- For protective purpose usage of SEAL Protective Laminates is recommended (ensure adequate drying before lamination). (12 hours drying time is recommended).
- Store unused media in the original packaging

ICC Profiles available for download at <http://www.SEAL.color-base.com>

For tech support with any of our inkjet print materials, please call SEAL Media Support at 800-257-7325, ext. 8945

Printability	
Eco Solvent	◆
UV-curable	◆
Latex	◆
Solvent	◆



Temperatures and thicknesses are given as approximate values. All data are standard values. The information in this specification sheet is based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customer tests will be required. A legally binding guarantee of specific properties is not to be inferred from our specifications. The information given here may be subject to change without notice. SEAL has not prepared MSDSs for these products which are not subject to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the SEAL directions for use, these products should not present a health and safety hazard. However, use or processing of the products in a manner not in accordance with the directions for use may affect their performance and present potential health and safety hazards. The purchaser should test material to determine if it is suitable for their own specific purpose.

December 2014